
Microperfetto IP66 Applique
6W 3000K 38°

Design: Aria Design Team





0,5 Kg

IP 66 IK 10

Product Code	Color
1915BW00W88	Brushed copper

General specifications

Product type	Outdoor spotlight
Mounting type	Wall-bracket
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Luce da facciata per esterni equipaggiata con LED COB e driver integrato. Installabile su facciate di edifici pubblici e privati. Risulta di semplice installazione e garantisce, grazie allo speciale trattamento antiossidante e alle guarnizioni siliconiche, un alto grado di protezione IP66. Può essere applicata con luce rivolta verso l'alto o verso il basso.
Applications	Porches , Walkways , Façades , Courtyards

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 730lm 6W 3000K CRI80
Nominal lumens on thermal regime (lm)	730
LOR	88
Delivered lumen (lm)	642
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	38°

Weight and dimension

Length (mm)	136
Width (mm)	56
Diameter (mm)	53
Weight (Kg)	0.5

Accessories



Product Code	28-4499-30
Name	Honeycomb


ARIA an IVELA brand

Via B. Buozzi, 15
20050 Liscate • Milano
T +39 02 9500121 • F +39 02 95001205
info@aria.lighting

Microperfetto IP66 Applique
6W 3000K 14°

Design: Aria Design Team





0,5 Kg

IP 66 IK 10

Product Code	Color
1915BZ00W88	Brushed copper

General specifications

Product type	Outdoor spotlight
Mounting type	Wall-bracket
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Luce da facciata per esterni equipaggiata con LED COB e driver integrato. Installabile su facciate di edifici pubblici e privati. Risulta di semplice installazione e garantisce, grazie allo speciale trattamento antiossidante e alle guarnizioni siliconiche, un alto grado di protezione IP66. Può essere applicata con luce rivolta verso l'alto o verso il basso.
Applications	Porches , Walkways , Façades , Courtyards

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 730lm 6W 3000K CRI80
Nominal lumens on thermal regime (lm)	730
LOR	88
Delivered lumen (lm)	642
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	14°


Weight and dimension

Length (mm)	136
Width (mm)	56
Diameter (mm)	53
Weight (Kg)	0.5

Microperfetto IP66 Applique
6W 3000K 14°

Design: Aria Design Team





0,5 Kg

IP 66 IK 10

Product Code	Color
1915BZ00W30	Black

General specifications

Product type	Outdoor spotlight
Mounting type	Wall-bracket
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Façade light equipped with COB LED and driver included. For outdoor applications on façades of public and residential buildings. Thanks to the special antioxidising treatment and the silicone gaskets, it's easy to install and guarantees a high protection rating IP66. It can be mounted both with up-light and down-light.
Applications	Squares , Façades , Courtyards

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 730lm 6W 3000K CRI80
Nominal lumens on thermal regime (lm)	730
LOR	88
Delivered lumen (lm)	642
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	14°

Weight and dimension

Length (mm)	136
Width (mm)	56
Diameter (mm)	53
Weight (Kg)	0.5


ARIA an IVELA brand

Via B. Buozzi, 15
20050 Liscate • Milano
T +39 02 9500121 • F +39 02 95001205
info@aria.lighting

Microperfetto IP66 Applique
6W 3000K 38°

Design: Aria Design Team





0,5 Kg

IP 66 IK 10

Product Code	Color
1915BW00W30	Black

General specifications

Product type	Outdoor spotlight
Mounting type	Wall-bracket
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Luce da facciata per esterni equipaggiata con LED COB e driver integrato. Installabile su facciate di edifici pubblici e privati. Risulta di semplice installazione e garantisce, grazie allo speciale trattamento antiossidante e alle guarnizioni siliconiche, un alto grado di protezione IP66. Può essere applicata con luce rivolta verso l'alto o verso il basso.
Applications	Porches , Walkways , Façades , Courtyards

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 730lm 6W 3000K CRI80
Nominal lumens on thermal regime (lm)	730
LOR	88
Delivered lumen (lm)	642
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	38°

Weight and dimension

Length (mm)	136
Width (mm)	56
Diameter (mm)	53
Weight (Kg)	0.5


ARIA an IVELA brand

Via B. Buozzi, 15
20050 Liscate • Milano
T +39 02 9500121 • F +39 02 95001205
info@aria.lighting

Microperfetto IP66 Applique
6W 3000K 14°

Design: Aria Design Team





0,5 Kg

IP 66 IK 10

Product Code	Color
1915BZ00W88	Mat white

General specifications

Product type	Outdoor spotlight
Mounting type	Wall-bracket
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Luce da facciata per esterni equipaggiata con LED COB e driver integrato. Installabile su facciate di edifici pubblici e privati. Risulta di semplice installazione e garantisce, grazie allo speciale trattamento antiossidante e alle guarnizioni siliconiche, un alto grado di protezione IP66. Può essere applicata con luce rivolta verso l'alto o verso il basso.
Applications	Porches , Walkways , Façades , Courtyards

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 730lm 6W 3000K CRI80
Nominal lumens on thermal regime (lm)	730
LOR	88
Delivered lumen (lm)	642
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	14°


Weight and dimension

Length (mm)	136
Width (mm)	56
Diameter (mm)	53
Weight (Kg)	0.5

Microperfetto IP66 Applique
6W 3000K 38°

Design: Aria Design Team





0,5 Kg

IP 66 IK 10

Product Code	Color
1915BW00W88	Mat white

General specifications

Product type	Outdoor spotlight
Mounting type	Wall-bracket
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Luce da facciata per esterni equipaggiata con LED COB e driver integrato. Installabile su facciate di edifici pubblici e privati. Risulta di semplice installazione e garantisce, grazie allo speciale trattamento antiossidante e alle guarnizioni siliconiche, un alto grado di protezione IP66. Può essere applicata con luce rivolta verso l'alto o verso il basso.
Applications	Porches , Walkways , Façades , Courtyards

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 730lm 6W 3000K CRI80
Nominal lumens on thermal regime (lm)	730
LOR	88
Delivered lumen (lm)	642
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	38°

Weight and dimension

Length (mm)	136
Width (mm)	56
Diameter (mm)	53
Weight (Kg)	0.5

Accessories



Product Code	28-4499-30
Name	Honeycomb

ARIA an IVELA brand

Via B. Buozzi, 15
20050 Liscate • Milano
T +39 02 9500121 • F +39 02 95001205
info@aria.lighting